



SSA11

Size	Load Index	Speed Symbols	Mold Tread Depth (mm)	Standard Rim	Max Load and Inflated Pressure				Inflation Section Width (mm)	Inflation Overall Diameter (mm)	Pattern
					Dual		Single				
					kg	kpa	kg	kpa			
11R22.5	16	146/143	M	14.5	8.25	2725	830	3000	830	279	1054
11R22.5	18	149/146	L	14.5	8.25	3000	930	3250	930	279	1054
11R24.5	16	149/146	M	14.5	8.25	3000	830	3250	830	279	1104
11R24.5	18	152/149	L	14.5	8.25	3250	930	3550	930	279	1104
295/75R22.5	16	146/143	M	15	9.00	2725	830	3000	830	298	1014
295/75R22.5	18	149/146	L	15	9.00	3000	930	3250	930	298	1014



SSD12

Size	Load Index	Speed Symbols	Mold Tread Depth (mm)	Standard Rim	Max Load and Inflated Pressure				Inflation Section Width (mm)	Inflation Overall Diameter (mm)	Pattern
					Dual		Single				
					kg	kpa	kg	kpa			
11R22.5	16	146/143	M	20.5	8.25	2725	830	3000	830	279	1065
11R22.5	18	149/146	L	20.5	8.25	3000	930	3250	930	279	1065
11R24.5	16	149/146	M	20.5	8.25	3000	830	3250	830	279	1116
11R24.5	18	152/149	L	20.5	8.25	3250	930	3550	930	279	1116



SSA21

Size	Load Index	Speed Symbols	Mold Tread Depth (mm)	Standard Rim	Max Load and Inflated Pressure				Inflation Section Width (mm)	Inflation Overall Diameter (mm)	Pattern
					Dual		Single				
					kg	kpa	kg	kpa			
295/80R22.5	18	152/149	M	16	9.00	3250	900	3550	830	298	1044
295/75R22.5	16	146/143	M	15	9.00	2725	830	3000	830	298	1014
295/75R22.5	18	149/146	L	15	9.00	3000	930	3250	930	298	1014



SSD72

Size	Load Index	Speed Symbols	Mold Tread Depth (mm)	Standard Rim	Max Load and Inflated Pressure				Inflation Section Width (mm)	Inflation Overall Diameter (mm)	Pattern
					Dual		Single				
					kg	kpa	kg	kpa			
295/75R22.5	16	146/143	M	22	9.00	2725	830	3000	830	298	1020
295/75R22.5	18	149/146	L	22	9.00	3000	930	3250	930	298	1020



SSM13

Size	Load Index	Speed Symbols	Mold Tread Depth (mm)	Standard Rim	Max Load and Inflated Pressure				Inflation Section Width (mm)	Inflation Overall Diameter (mm)	Pattern
					Dual		Single				
					kg	kpa	kg	kpa			
11R22.5	16	146/143	M	15.5	8.25	2725	830	3000	830	279	1054
11R22.5	18	149/146	L	15.5	8.25	3000	930	3250	930	279	1054
11R24.5	16	149/146	M	15.5	8.25	3000	830	3250	830	279	1104
11R24.5	18	152/149	L	15.5	8.25	3250	930	3550	930	279	1104